

ISO/IEC 19798 Yield Test Report

EPSON Color Laser Printer AL-C4200

Cartridge Code:

Yellow(Y)	C13S050242	Magenta(M)	C13S050243
Cyan(C)	C13S050244	Black(K)	C13S050245

Declaration of yield:

Average Continuous Composite Color(YMC) Cartridge Yield	13200	standard pages
Average Continuous Black Cartridge(K) Yield	11700	standard pages
Declared yield value in accordance with ISO/IEC 19798		

Tested Cartridge Summary:

90% Lower Confidence:

Yellow Cartridge:	13092	standard pages
Magenta Cartridge:	11835	standard pages
Cyan Cartridge:	15365	standard pages
Black Cartridge:	11768	standard pages

Date Tasted: 2006.08.31 ~ 2006.10.13

For questions concerning testing contact:

SEIKO EPSON CORPORATION
80 Harashinden, Hirooka, Shiojiri-shi, Nagano-ken 399-0785 JAPAN
Attn: Page Printer Marketing Department

Number of cartridges used in testing:	Y=9	M=9	C=9	K=9
Number of cartridges used in calculations:	Y=9	M=9	C=9	K=9
Shake procedure used?	No			
Print mode:	Continuous (500pages/job)			
Number of engines used in testing:	3			
Media used:	82gsm			
Paper size:	A4			
Paper feed orientation:	Short edge feed			
Computer model:	EPSON DOS/V_2.4GHz			
Driver version:	AcuLaser C4200 Driver WHQL Certified (1.0b)			
Operating system:	Microsoft Windows 2000			
Application software	Adobe Reader Ver.7.0.1			
Test page version	ISO-IEC 24712 FCD Test Suite.pdf 2005/10/05			
Power (off/ on) everyday	Yes			

Cartridge Testing Data:

Engine	Color	Cartridge	Temperature			Humidity			Cartridge Yield	Cart Used in Calculation
			Min	Max	Avg	Min	Max	Avg		
GMYZ100389	Y	2221100238	20.7	22.0	21.3	52	65	56	11410	Y
GMYZ100389	Y	2221100239	20.1	22.9	21.9	51	65	55	11630	Y
GMYZ100389	Y	2221100244	21.4	22.0	21.7	51	65	61	12365	Y
GMYZ101082	Y	2221100241	20.1	21.9	21.3	52	65	57	14260	Y
GMYZ101082	Y	2221100242	20.5	22.9	22.0	51	65	57	14890	Y
GMYZ101082	Y	2221100243	21.4	23.7	21.9	45	65	62	14815	Y
GMYZ100004	Y	2221100240	20.1	21.9	21.3	52	65	57	16725	Y
GMYZ100004	Y	2221100245	20.5	22.9	21.9	51	65	59	17495	Y
GMYZ100004	Y	2221100258	21.4	23.7	22.1	45	65	60	18475	Y
GMYZ100389	M	2222100063	20.7	22.0	21.3	52	65	57	10500	Y
GMYZ100389	M	2222100064	20.1	21.9	21.3	52	65	56	10350	Y
GMYZ100389	M	2222100062	20.9	22.9	22.1	51	63	56	10990	Y
GMYZ101082	M	2222100060	20.1	21.9	21.3	52	65	57	14370	Y
GMYZ101082	M	2222100061	20.5	22.9	22.0	51	63	56	14145	Y
GMYZ101082	M	2222100080	21.4	22.9	21.8	57	65	62	14305	Y
GMYZ100004	M	2222100058	20.7	21.9	21.4	52	65	57	13550	Y
GMYZ100004	M	2222100059	20.1	22.9	21.9	51	65	55	13940	Y
GMYZ100004	M	2222100065	21.4	22.9	21.8	57	65	62	14170	Y
GMYZ100389	C	2222100034	20.7	21.9	21.4	52	65	57	13415	Y
GMYZ100389	C	2222100088	20.1	22.9	21.9	51	65	55	13940	Y
GMYZ100389	C	2222100089	21.4	22.9	21.8	57	65	62	13835	Y
GMYZ101082	C	2222100092	20.1	22.7	21.7	52	65	55	16220	Y
GMYZ101082	C	2222100091	21.4	22.9	21.7	51	65	61	16970	Y
GMYZ101082	C	2222100090	21.4	23.7	22.1	45	65	60	17445	Y
GMYZ100004	C	2222100094	20.1	22.9	21.8	51	65	56	23695	Y
GMYZ100004	C	2222100095	21.3	23.7	21.9	45	65	61	27965	Y
GMYZ100004	C	2222100096	20.4	23.0	21.6	54	64	62	29305	Y
GMYZ100389	K	2221100169	20.7	22.0	21.4	52	65	57	11520	Y
GMYZ100389	K	2221100167	20.1	22.7	21.8	52	65	55	12665	Y
GMYZ100389	K	2221100168	21.4	22.9	21.8	51	65	59	12255	Y
GMYZ101082	K	2221100170	20.7	22.0	21.4	52	65	56	12060	Y
GMYZ101082	K	2221100174	20.1	22.9	21.9	51	65	55	11890	Y
GMYZ101082	K	2221100171	21.4	22.0	21.7	51	65	61	11500	Y
GMYZ100004	K	2221100172	20.7	21.9	21.4	52	65	57	12585	Y
GMYZ100004	K	2221100173	20.1	22.9	21.9	51	65	55	12215	Y
GMYZ100004	K	2221100175	21.4	22.1	21.7	57	65	62	11645	Y

	Average	Std Dev. Of Sample	90% Lower Confidence
Yellow Cartridge	14674	2552	13092
Magenta Cartridge	12924	1757	11835
Cyan Cartridge	19199	6185	15365
YMC Composite			13277
Black Cartridge	12037	434	11768

Comments: